



Nemasub

Regulators & Accessories

2010

“Our goal is to deliver high performance, high quality products that offer the lowest total cost of ownership...”

BESTAŞ A.Ş.


SİFTAH SK. NO:9 34710 Kadıköy
İSTANBUL - TURKEY

Phones: +90 216 449 00 30
+90 216 336 60 54

Fax: +90 216 347 39 61

E-mail: scuba@bestas.com

Web: <http://www.nemo-sub.com>



FIRST STAGE REGULATORS

THE BALANCED DIAPHRAGM 1ST STAGE REGULATOR



• RG 1002 DIN

Technical Specifications:

TYPE	:	DIAPHRAGM BALANCED FIRST STAGE SWIVEL CHAMBER
VENTILATION RATE	:	AIR SUPPLY / 3000 PSI: 135SCFM
INTERMEDIATE PRESSURE	:	135 - 145 PSI
HIGH PRESSURE PORT	:	(7/16 - 20) x 2
LOW PRESSURE PORT	:	(3/8 - 24) x 4



• RG 1002 YOKE

THE PISTON FIRST STAGE REGULATOR




• RG 1007 DIN

Technical Specifications:

TYPE	:	FLOW THROUGH PISTON FIRST STAGE
VENTILATION RATE	:	AIR SUPPLY / 3000 PSI: 135SCFM
INTERMEDIATE PRESSURE	:	135 - 145 PSI
HIGH PRESSURE PORT	:	(7/16 - 20) x 1
LOW PRESSURE PORT	:	(3/8 - 24) x 4



• RG 1007 YOKE



FIRST STAGE REGULATORS

THE BALANCED DIAPHRAGM FIRST STAGE REGULATOR



• RG 1005 YOKE



• RG 1005 DIN

Technical Specifications:

TYPE	: DIAPHRAGM BALANCED FIRST STAGE
VENTILATION RATE	: AIR SUPPLY / 3000 PSI: 135SCFM
INTERMEDIATE PRESSURE	: 135 - 145 PSI
HIGH PRESSURE PORT	: (7/16 - 20) x 2
LOW PRESSURE PORT	: (3/8 - 24) x 4

THE BALANCED DIAPHRAGM FIRST STAGE REGULATOR




• RG 1008 YOKE-ICE



• RG 1008 DIN-ICE

Technical Specifications:

TYPE	: DIAPHRAGM BALANCED FIRST STAGE
VENTILATION RATE	: AIR SUPPLY / 3000 PSI: 135SCFM
INTERMEDIATE PRESSURE	: 135 - 145 PSI
HIGH PRESSURE PORT	: (7/16 - 20) x 2
LOW PRESSURE PORT	: (3/8 - 24) x 4



FIRST STAGE REGULATORS

THE BALANCED DIAPHRAGM FIRST STAGE REGULATOR

- RG 2001 - ICE

Technical Specifications:

TYPE	: DIAPHRAGM BALANCED FIRST STAGE
VENTILATION RATE	: AIR SUPPLY / 3000 PSI: 135SCFM
INTERMEDIATE PRESSURE	: 135 - 160 PSI
HIGH PRESSURE PORT	: (7/16 - 20) x 2
LOW PRESSURE PORT	: (3/8 - 24) x 4



THE BALANCED DIAPHRAGM FIRST STAGE REGULATOR




- RG 2002 YOKE

Technical Specifications:

TYPE	: DIAPHRAGM BALANCED FIRST STAGE
VENTILATION RATE	: AIR SUPPLY / 3000 PSI: 135SCFM
INTERMEDIATE PRESSURE	: 135 - 145 PSI
HIGH PRESSURE PORT	: (7/16 - 20) x 2
LOW PRESSURE PORT	: (3/8 - 24) x 4





SECOND STAGE REGULATORS

COMPACT FLAT DESIGNED OCTOPUS SECOND STAGE REGULATOR FOR LEFT/RIGHT HANDED



- RG6L
(FOR LEFT HANDED)



- RG6R
(FOR RIGHT HANDED)

Technical Specifications:

TYPE	: DOWNSTREAM DEMAND VALVE
INTERMEDIATE PRESSURE	: 145 PSI
CRACKING EFFORT	: 1.0 - 2.0 CIW
PRESETTING	: 1.5 CIW
FLOW RATE	: AIR SUPPLY / 3000 PSI:135CFM


OCTOPUS, BCD POWER INFLATOR HOSE COMPATIBLE SECOND STAGE REGULATOR

- RG6-BC OCTOPUS



Technical Specifications:

TYPE	: DOWNSTREAM DEMAND VALVE WITH TWIN AIR INTAKE
INTERMEDIATE PRESSURE	: 145 PSI
CRACKING EFFORT	: 1.5 - 2.0 CIW (Column inches of Water)
PRESETTING	: 1.5 CIW
FLOW RATE	: 30 + SCFM (Air Supply:3000 PSI)



SECOND STAGE REGULATORS

NON-ADJUSTABLE SECOND STAGE REGULATOR



• RG 3



Technical Specifications:

TYPE	: DOWNSTREAM DEMAND VALVE
INTERMEDIATE PRESSURE	: 145 PSI
CRACKING EFFORT	: 1.5 - 2.0 CIW (Column inches of Water)
PRESETTING	: 1.5 CIW
FLOW RATE	: 30 + SCFM (Air Supply:3000 PSI)

NON-ADJUSTABLE SECOND STAGE REGULATOR




• RG 8



Technical Specifications:

TYPE	: OCTOPUS ALL DIRECTION WITH OR WITHOUT SWIVEL
INTERMEDIATE PRESSURE	: 145 PSI
CRACKING EFFORT	: 0.8 - 1.4 CIW (Column inches of Water)
WOB@50m	: 0.8 J/L
FLOW RATE	: 30 + SCFM (Air Supply:3000 PSI)



SECOND STAGE REGULATORS

ADJUSTABLE SECOND STAGE REGULATOR FOR HARD-CORE DIVER IN EXTREME ENVIRONMENT



Technical Specifications:

TYPE	:	DOWNSTREAM DEMAND VALVE WITH TWIN AIR INTAKE
INTERMEDIATE PRESSURE	:	145 PSI
CRACKING EFFORT	:	1.0 - 2.0 CIW (Column inches of Water)
WOB@50m	:	0.95 J/L
FLOW RATE	:	30 + SCFM (Air Supply:3000 PSI)

- RG-9, RG-9 ICE


NON-ADJUSTABLE SECOND STAGE REGULATOR



- RG 10

Technical Specifications:

TYPE	:	DOWNSTREAM DEMAND VALVE WITH TWIN AIR INTAKE
INTERMEDIATE PRESSURE	:	145 PSI
CRACKING EFFORT	:	1.0 - 2.0 CIW (Column inches of Water)
PRESETTING	:	1.5 CIW
FLOW RATE	:	30 + SCFM (Air Supply: 3000 PSI)



SECOND STAGE REGULATORS

PNEUMATIC BALANCED SECOND STAGE REGULATOR



• RG-11




Technical Specifications:

INTERMEDIATE PRESSURE	: 145 PSI
CRACKING EFFORT	: 0.8 - 1.4 CIW
WOB@50m	: 0.8 J/L
FLOW RATE	: 30+SCFM (Air Supply: 3000 PSI)

NEMOSUB LOW PRESSURE HOSES

Code	Length	Lenght	Max. Pressure	Color
LP-27	27"	68,58 cm	250 PSI	Black
LP-29	29"	73,66 cm	250 PSI	Black
LP-31	31"	78,74 cm	250 PSI	Black
LP-36S	36"	91,44 cm	250 PSI	Yellow
LP-41S	41"	104,14 cm	250 PSI	Yellow





REGULATOR ACCESSORIES

AQUATEC® AF-100 GUARDIAN AIR FILTER



Clean Air System


The Aquatec Guardian Air Filter was designed to cleanse high pressure compressed air for use by scuba divers. The system is easy to install and maintain. The Guardian Air Filter is only for recreational air diving use to depths not in excess of 130 feet of sea-water/ 40 meters.

Warning:

Do not use the Guardian Air Filter with enriched air Nitrox or for any other mixed gas diving. Patent No. 210808

Suggestion:

Replace the Air filter cartridge for every 50 times dives or every 6 months whichever comes first.



REGULATOR ACCESSORIES

NEMOSUB® P14

Intermediate Pressure Gauge



NEMOSUB® DY-01

Din To Yoke Converter



NEMOSUB® Din 300

**Din Fitting Wheel 300 Bar for First Stage
Regulator**



NEMOSUB® SW-01X 360° Swivel Attachment to 2nd Stage



NEMOSUB® SW-04X Swivel Attachment to 2nd Stage



HF-05 9/16" Male to 3/8" Female Thread Converter




HF-06 9/16" Male to 3/8" Female Thread Converter



HF-011 9/16" Male to 3/8" Female Thread Converter





REGULATOR ACCESSORIES



NEMOSUB[®] P7

Clear Silicone Mouth Piece



NEMOSUB[®] P8

Black Silicone Mouth Piece



NEMOSUB[®] P9

Black Silicone Long Neck Mouth Piece



NEMOSUB[®] P42

Black Silicone Mouth Piece




NEMOSUB[®] P10

Silicone Colored Tooth Mouth Piece

**Tooth Color:
Black / Orange / Blue / Yellow**



Mouth Piece Clips



REGULATOR ACCESSORIES

NEMOSUB[®] HP-01

P.V.C. Hose Protector for First Stage

Black - Yellow



NEMOSUB[®] HP-02

PVC Hose Protector for 2nd Stage

Black - Yellow



NEMOSUB[®] HP-200

Hose Protector - Black



NEMOSUB[®] HR-01

Hose Wrap

Black - Yellow



NEMOSUB[®] KIT-01

NBR O-Ring Kit, 38 Sizes



The background is a deep blue underwater scene filled with many fish of various species, including some larger ones with prominent eyes. Overlaid on the right side is a white graphic consisting of numerous thin, curved lines that form a large, abstract shape resembling a stylized 'S' or a flowing ribbon. The text is positioned in the upper left quadrant, overlaid on the blue background.

“Our goal is to deliver high performance, high quality products that offer the lowest total cost of ownership...”

BESTAŞ A.Ş.

SİFTAH SK. NO:9 34710 Kadıköy
İSTANBUL - TURKEY

Phones: +90 216 449 00 30
+90 216 336 60 54
Fax: +90 216 347 39 61
E-mail: scuba@bestas.com
Web: <http://www.nemo-sub.com>